

# NipFoil-D



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Production of plastic film, adhesives and flexible packaging : conveyor, contact and lay-on rollers for winding
<b>Hardness Range:</b>	65, 80 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	Standard 15 mm
<b>Temperature resistance:</b>	Dry: continuous 110°C / peak 130°C Wet: continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Special double layer technology with very soft base layer to reduce wrinkle formation during winding  Harder outside layer assures good abrasion resistance and long lifetime  Entirely antistatic  Good and neutral behavior in contact with plastic film
<b>Specific characteristics:</b>	Antistatic
<b>Chemical resistance:</b>	Acid solutions: Excellent Alkaline solutions: Excellent Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent Alcohols (ethanol, IPA,...): Excellent Ageing resistance: Excellent
<b>Recommended cleaning products:</b>	(Hot) water, acid and alkaline cleaners, IPA and alcohol, MEC, ether, ethyl acetate