

HanneStar Plus



Cover Type:	Rubber	
Possible applications:	<p>Rollers submitted to mechanical load and in contact with oil or grease of mineral and animal origin, also at higher temperature.</p> <p>Areas of application : metal and aluminium industry, conveyor systems, food and meat processing, wood industry, conversion of PVC and plastic film etc.</p>	
Hardness Range:	65, 70, 80, 85, 92, 95, 97 Shore A	
Recommended Cover Thickness:	min. 10 mm - max. 20 mm	
Temperature resistance:	Dry:	continuous 100°C / peak 110°C
	Wet:	continuous 70°C / peak 80°C
Properties and advantages:	<p>Very good physical properties, good tear and cut-in resistance</p> <p>Excellent resistance to mineral, vegetable and synthetic oils. Very good resistance to kerosine and fuels</p> <p>Good resistance to diluted acids and to alkaline solutions</p>	
Chemical resistance:	Acid solutions:	Good
	Alkaline solutions:	Good
	Hot water and steam:	Good
	Ozone:	Very good
	Oil and grease:	Excellent
	Aromatic solvents (toluene, benzene,...):	Moderate
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	