


# WoodCoat-S



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Production of wood, wood board and wood laminate : - varnishing rollers, UV lacquering, decorative coating, impregnation - glue applicators, water or solvent based - catalyst and primer application  Possibility to foresee microgrooves up to 80 grooves/inch  Not recommended for oiling of wood
<b>Hardness Range:</b>	35, 45, 55, 65, 75 Shore A
<b>Available Colours:</b>	green
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 120°C / peak 130°C Wet: continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Good physical properties  Excellent resistance to polar solvents (MEC, acetates, alcohols...)  Very good surface wetting and transfer properties  High purity and homogeneity  Easy to grind and to groove
<b>Chemical resistance:</b>	Acid solutions: Excellent Alkaline solutions: Excellent Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent Alcohols (ethanol, IPA,...): Excellent Ageing resistance: Exceptional
<b>Recommended cleaning products:</b>	(Warm) water, soap, detergent, acid/alkaline cleaners, polar solvents : MEK, alcohol, acetate...