


MultiCoat-SP



Cover Type:	Rubber	
Possible applications:	<p>Wood and wood laminate, PVC flooring production : varnishing rollers, glue applicators</p> <p>Conversion of paper and film – adhesive and release stock : primer, glue and silicone applicator rollers and sleeves</p> <p>All converting of (printed) paper, board, film and flexible packaging : applicator, coater and (UV) varnishing rollers and sleeves, backing rollers and sleeves</p>	
Hardness Range:	30, 40, 50, 60, 70 Shore A	
Recommended Cover Thickness:	min. 15 mm - max. 30 mm	
Temperature resistance:	Dry: Wet:	continuous 80°C / peak 110°C continuous 90°C / peak 125°C
Properties and advantages:	<p>Good physical properties</p> <p>Excellent resistance to polar solvents (MEC, acetates, alcohols...)</p> <p>Very good surface wetting and transfer properties</p> <p>High purity and homogeneity</p>	
Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...):	Very good Very good Very good Excellent Not suited Not suited Not suited Excellent
Recommended cleaning products:	(Warm) water, soap, detergent, acid/alkaline cleaners, polar solvents : MEK, alcohol, acetate...	