


# HannElast-SP



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Rollers and drums for transport systems, drive rollers for transport belts, rollers for packaging machines Wheels, pulleys, wheel treading Winder drums for the textile and décor industry (carpet, PVC floor covering...) Diverse applications where good abrasion resistance is needed, in dry or humid conditions (no oil or fat !)
<b>Hardness Range:</b>	60, 70, 80, 90 Shore A
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 80°C / peak 95°C Wet: continuous 60°C / peak 70°C
<b>Properties and advantages:</b>	Very good physical properties, very good abrasion and tear resistance Not suited for contact with oil and grease
<b>Chemical resistance:</b>	Acid solutions: Very good Alkaline solutions: Good Hot water and steam: Good Ozone: Moderate Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Good
<b>Recommended cleaning products:</b>	Water, warm water, soap and detergents, alcohol based cleaners, acid based cleaners
<b>Remark:</b>	W przypadku niektórych ściernic możliwa jest praca z większą grubością warstwy (do 50 mm), po obliczeniu obciążenia. Skontaktuj się z nami, aby uzyskać więcej informacji