


# HanneDrive HP



<b>Cover Type:</b>	Special rubber
<b>Possible applications:</b>	Helper, Wire Driving roll on a loaded nip position
<b>Hardness Range:</b>	12, 20, 25, 30, 35, 40, 45, 65 PJ
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 90°C / peak 120°C
<b>Properties and advantages:</b>	Abrasion resistance Resistance to shocks and impacts Hardness and profile stability in operation Developped for high loaded nip position
<b>Doctoring:</b>	HDPE blade: at 1 to 2 mm from surface if loading necessary : angle 16 to 20 deg, load 50 to 70 (maxi 100) N/m (Dry doctoring prohibited)
<b>Possible surface design:</b>	Plain, Suction (S)
<b>Chemical resistance:</b>	Acid solutions: Good Alkaline solutions: Good Hot water and steam: Good Ozone: Good Oil and grease: Excellent Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited
<b>Recommended cleaning products:</b>	Good resistance to standard chemicals normally used in paper machines
<b>Remark:</b>	Reference list available on demand