

# Bacroll



|                                       |  |
|---------------------------------------|--|
| <b>Cover Type:</b>                    | Rubber   |
| <b>Possible applications:</b>         | Textile industry - sizing of yarns : dip and squeeze rollers<br>Recommended solution for the dip roller postions   |
| <b>Hardness Range:</b>                | 62, 69, 79 Shore A   |
| <b>Available Colours:</b>             | black  |
| <b>Recommended Cover Thickness:</b>   | min. 10 mm - max. 20 mm  |
| <b>Temperature resistance:</b>        | Dry: continuous 105°C / peak 115°C<br>Wet: continuous 90°C / peak 100°C  |
| <b>Properties and advantages:</b>     | Very good chemical resistance to sizing products, both for natural as for synthetic yarns, up to 100 °C<br><br>Very good mechanical properties, abrasion and tear resistance<br><br>Non-staining   |
| <b>Chemical resistance:</b>           | Acid solutions: Moderate<br>Alkaline solutions: Very good<br>Hot water and steam: Very good<br>Ozone: Excellent<br>Oil and grease: Excellent<br>Aromatic solvents (toluene, benzene,...): Moderate<br>Chlorinated solvents: Moderate<br>Polar solvents (MEC, ether, acetate,...): Not suited<br>Alcohols (ethanol, IPA,...): Very good<br>Ageing resistance: Excellent |
| <b>Recommended cleaning products:</b> | (Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit   |
| <b>Remark:</b>                        | Bacroll-HP : special multi-layer solution for high load applications   |