



<b>Cover Type:</b>	Rubber	
<b>Possible applications:</b>	Textile industry - sizing of yarns : dip and squeeze rollers Recommended solution for the dip roller postions	
<b>Hardness Range:</b>	62, 69, 79 Shore A	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 105°C / peak 115°C continuous 90°C / peak 100°C
<b>Properties and advantages:</b>	<p>Very good chemical resistance to sizing products, both for natural as for synthetic yarns, up to 100 °C</p> <p>Very good mechanical properties, abrasion and tear resistance</p> <p>Non-staining</p>	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...): Ageing resistance:	Moderate Very good Very good Excellent Excellent Moderate Moderate Not suited Very good Excellent
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	
<b>Remark:</b>	Bacroll-HP : special multi-layer solution for high load applications	