



<b>Cover Type:</b>	Special rubber	
<b>Possible applications:</b>	Tissue paper converting : embossing rollers, especially for polyvalent converting lines (toilet paper, kitchen towels...)	
<b>Hardness Range:</b>	55 Shore A	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry:	continuous 110°C / peak 125°C
<b>Properties and advantages:</b>	<p>Increased elasticity allows easy matching with different product configurations</p> <p>Suitable for a wide range of load</p> <p>Guarantees perfect thickness of the substrate</p> <p>Excellent abrasion and mechanical stress resistance assure long lifetime</p> <p>Faithful pattern reproduction, allows high as well as micro-embossing</p> <p>Suitable for high speed lines (up to 800 m/min)</p>	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...): Ageing resistance:	Very good Good Good Very good Good Not suited Not suited Not suited Very good Very good
<b>Recommended cleaning products:</b>	(Warm) water, soap, industrial cleaners and detergents, alcohol, (diluted) acid cleaners	
<b>Remark:</b>	Multiplast-D and Multiplast-T : multilayer solutions for optimized results in specific, demanding applications	