

# Press Plast



<b>Cover Type:</b>	Special rubber
<b>Possible applications:</b>	Plastic film and adhesives industry : nip and laminator rollers
<b>Hardness Range:</b>	65, 85, 90, 95 Shore A
<b>Available Colours:</b>	green, blue
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 125°C / peak 140°C
<b>Properties and advantages:</b>	Excellent resistance to high mechanical load Very high abrasion resistance and lifetime Excellent shape stability, fast recovery after deformation Suited for use on high speed lines (1000 m/min and more)
<b>Chemical resistance:</b>	Acid solutions: Very good Alkaline solutions: Good Hot water and steam: Good Ozone: Very good Oil and grease: Good Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Very good Ageing resistance: Very good
<b>Recommended cleaning products:</b>	(Warm) water, soap, industrial cleaners and detergents, alcohol, (diluted) acid cleaners
<b>Remark:</b>	Press Plast D : special multilayer solution for demanding applications