



<b>Cover Type:</b>	Rubber	
<b>Possible applications:</b>	Tissue paper converting : glue applicator	
<b>Hardness Range:</b>	50, 62, 65, 69, 70, 80 Shore A	
<b>Available Colours:</b>	black	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry:	continuous 100°C / peak 110°C
	Wet:	continuous 70°C / peak 80°C
<b>Properties and advantages:</b>	Optimal glue transfer, homogeneous coating Excellent wettability and low surface roughness Product softness is preserved thanks to lower glue consumption Excellent dimensional stability Very good lifetime, good abrasion resistance Limited dust clogging, less cleaning needed Outstanding chemical compatibility (including lubrication oil) Very precise dimensional tolerances can be met	
<b>Specific characteristics:</b>	Glue repellent/non-stick properties	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...):	Good Very good Good Good Excellent Moderate Not suited Not suited Very good
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	