



Cover Type:	Rubber	
Possible applications:	Tissue paper converting : glue applicator	
Hardness Range:	50, 62, 65, 69, 70, 80 Shore A	
Recommended Cover Thickness:	min. 10 mm - max. 20 mm	
Temperature resistance:	Dry:	continuous 100°C / peak 110°C
	Wet:	continuous 70°C / peak 80°C
Properties and advantages:	Optimal glue transfer, homogeneous coating Excellent wettability and low surface roughness Product softness is preserved thanks to lower glue consumption Excellent dimensional stability Very good lifetime, good abrasion resistance Limited dust clogging, less cleaning needed Outstanding chemical compatibility (including lubrication oil) Very precise dimensional tolerances can be met	
Specific characteristics:	Glue repellent/non-stick properties	
Chemical resistance:	Acid solutions:	Good
	Alkaline solutions:	Very good
	Hot water and steam:	Good
	Ozone:	Good
	Oil and grease:	Excellent
	Aromatic solvents (toluene, benzene,...):	Moderate
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Very good
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, turpentine, white spirit	