



<b>Cover Type:</b>	Special rubber	
<b>Possible applications:</b>	Textile industry : wet finishing processes on fabric : hold-down and squeezing rollers in closed atmosphere applications (desizing, washing, bleaching, mercerizing)	
<b>Hardness Range:</b>	80 Shore A	
<b>Available Colours:</b>	yellow	
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 125°C / peak 140°C peak 100°C
<b>Properties and advantages:</b>	<p>Maximum temperature under steam condition : 110 °C</p> <p>Outstanding resistance to the main textile auxiliary products used in closed atmosphere at high temperature</p> <p>Good abrasion resistance, excellent lifetime, constant performance all along the lifetime</p> <p>Good temperature aging resistance</p> <p>Non-staining</p>	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...): Ageing resistance:	Good Very good Very good Excellent Good Not suited Not suited Not suited Very good Excellent
<b>Recommended cleaning products:</b>	(Warm) water, soap, industrial cleaners and detergents, alcohol, acid and alkaline cleaners	