

# Textractor



<b>Cover Type:</b>	Special rubber
<b>Possible applications:</b>	Textile industry : wet finishing processes on fabric : intermediate and final squeegee foulard rollers  Suited for knitted open and tubular fabrics
<b>Hardness Range:</b>	69, 92, 95 Shore A
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 110°C / peak 125°C Wet: continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Outstanding squeezing rate, increased squeezing efficiency, energy saving  Homogeneous and constant squeezing  Outstanding chemical resistance to main textile auxiliary products  High wear and aging resistance, high mechanical stress resistance  Non-staining
<b>Chemical resistance:</b>	Acid solutions: Good Alkaline solutions: Very good Hot water and steam: Very good Ozone: Very good Oil and grease: Good Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Very good Ageing resistance: Very good
<b>Recommended cleaning products:</b>	(Warm) water, soap, industrial cleaners and detergents, alcohol, acid and alkaline cleaners