

Textractor



Cover Type:	Special rubber	
Possible applications:	Textile industry : wet finishing processes on fabric : intermediate and final squeegee foulard rollers Suited for knitted open and tubular fabrics	
Hardness Range:	69, 93, 95, 98 Shore A	
Recommended Cover Thickness:	min. 12 mm - max. 25 mm	
Temperature resistance:	Dry:	continuous 110°C / peak 125°C
	Wet:	continuous 80°C / peak 90°C
Properties and advantages:	Outstanding squeezing rate, increased squeezing efficiency, energy saving Homogeneous and constant squeezing Outstanding chemical resistance to main textile auxiliary products High wear and aging resistance, high mechanical stress resistance Non-staining	
Chemical resistance:	Acid solutions:	Good
	Alkaline solutions:	Very good
	Hot water and steam:	Very good
	Ozone:	Very good
	Oil and grease:	Good
	Aromatic solvents (toluene, benzene,...):	Not suited
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Very good
	Ageing resistance:	Very good
Recommended cleaning products:	(Warm) water, soap, industrial cleaners and detergents, alcohol, acid and alkaline cleaners	