

# Textractor N



<b>Cover Type:</b>	Special rubber	
<b>Possible applications:</b>	Textile industry : wet finishing processes on fabric: final squeegee foulard rollers - for improved lifetime and efficiency, for very high mechanical load	
<b>Hardness Range:</b>	95 Shore A	
<b>Available Colours:</b>	blue	
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm	
<b>Temperature resistance:</b>	Dry:	continuous 125°C / peak 140°C
	Wet:	continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Outstanding squeezing rate, increased squeezing efficiency, energy saving  Homogeneous and constant squeezing  Outstanding wear and aging resistance, very high mechanical stress resistance  Non-staining	
<b>Chemical resistance:</b>	Acid solutions:	Good
	Alkaline solutions:	Moderate
	Hot water and steam:	Good
	Ozone:	Very good
	Oil and grease:	Moderate
	Aromatic solvents (toluene, benzene,...):	Not suited
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Very good
	Ageing resistance:	Excellent
<b>Recommended cleaning products:</b>	(Hot) water, soap, diluted acid or alkaline cleaners, industrial detergents	