

# Textractor N



<b>Cover Type:</b>	Special rubber	
<b>Possible applications:</b>	Textile industry : wet finishing processes on fabric: final squeegee foulard rollers - for improved lifetime and efficiency, for very high mechanical load	
<b>Hardness Range:</b>	95 Shore A	
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 125°C / peak 140°C continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Outstanding squeezing rate, increased squeezing efficiency, energy saving  Homogeneous and constant squeezing  Outstanding wear and aging resistance, very high mechanical stress resistance  Non-staining	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...): Ageing resistance:	Good Moderate Good Very good Moderate Not suited Not suited Not suited Very good Excellent
<b>Recommended cleaning products:</b>	(Hot) water, soap, diluted acid or alkaline cleaners, industrial detergents	