

Top Squeeze 2



Cover Type:	Special rubber	
Possible applications:	Steel, stainless steel, aluminium and non-ferrous coil production & conversion : squeegee, deflector and sink rollers in chemical environment (acid, alkaline, water rinse, quench) Pickling, cleaning, tin and zinc plating, annealing and galvanizing lines	
Hardness Range:	80 Shore A	
Available Colours:	green	
Recommended Cover Thickness:	min. 15 mm - max. 30 mm	
Temperature resistance:	Dry: Wet:	continuous 100°C / peak 115°C continuous 80°C / peak 90°C
Properties and advantages:	Excellent abrasion resistance, high cut and shear resistance Good chemical resistance (acid and alkaline environment) Good dynamic performance in wringer and squeegee applications	
Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...):	Good Very good Good Good Good Not suited Not suited Not suited Very good
Recommended cleaning products:	(Warm) water, soap, industrial cleaners and detergents, alcohol, (diluted) acid cleaners	
Remark:	Local solution, equivalent to Smartsqueeze	