

Top Squeeze 2



Cover Type:	Special rubber	
Possible applications:	Steel, stainless steel, aluminium and non-ferrous coil production & conversion : squeegee, deflector and sink rollers in chemical environment (acid, alkaline, water rinse, quench) Pickling, cleaning, tin and zinc plating, annealing and galvanising lines	
Hardness Range:	80 Shore A	
Recommended Cover Thickness:	min. 15 mm - max. 30 mm	
Temperature resistance:	Dry:	continuous 100°C / peak 115°C
	Wet:	continuous 80°C / peak 90°C
Properties and advantages:	Excellent abrasion resistance, high cut and shear resistance Good chemical resistance (acid and alkaline environment) Good dynamic performance in wringer and squeegee applications	
Chemical resistance:	Acid solutions:	Good
	Alkaline solutions:	Very good
	Hot water and steam:	Good
	Ozone:	Good
	Oil and grease:	Good
	Aromatic solvents (toluene, benzene,...):	Not suited
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Very good
Recommended cleaning products:	(Warm) water, soap, industrial cleaners and detergents, alcohol, (diluted) acid cleaners	
Remark:	Local solution, equivalent to Smartsqueeze	