


# RollMet-NS



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	<p>Production of metal strip: pinch rolls, hold-down rolls, steering, bridle and detour rolls, conveyor rollers, oil distribution and wipe-off rolls, squeegee rolls in different environments</p> <p>Specifically recommended in contact with oil and when clear colour or non-staining properties are requested</p> <p>Recommended for mechanical rollers on coil and colour coating lines</p>
<b>Hardness Range:</b>	65, 75, 80, 85, 90 Shore A
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 100°C / peak 110°C Wet: continuous 70°C / peak 80°C
<b>Properties and advantages:</b>	<p>Excellent resistance to mineral and vegetable oil, fuel, grease and (animal) fat</p> <p>Very good physical properties, tear and abrasion resistance, good elasticity and resilience</p> <p>Non-staining in contact with delicate substrates</p> <p>Good and stable grip in contact with most substrates</p> <p>Very good squeegee and wipe-off behaviour</p>
<b>Chemical resistance:</b>	Acid solutions: Moderate Alkaline solutions: Good Hot water and steam: Moderate Ozone: Good Oil and grease: Excellent Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Very good
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, turpentine, white spirit
<b>Remark:</b>	Suited for NaOH and KOH solutions up to 5 % concentration, at temperature of max. 75 °C